Callibo®

durable. innovative. elegant.

Calliclad



Durability of composite cement

The calliclad planks offer timeless beauty and are suitable for a wide range of applications both outdoors and indoors. Their high quality finish and durability are a guarantee of success.



Gabels



Extensions



Façade



Garden sheds



Comptoir du Bâtiment nv Kuiermansstraat 1, 1880 Kapelle-op-den-Bos, Belgium Tel: + 32 15 71 74 80 info@callibo.com





The charm of wood with the durability of composite cement



Calliclad is a decorative composite cement plank of high quality for multi purpose cladding uses.

For cladding and transforming brick walls, garden sheds, garden walls, extensions, gables, eaves and facades. For DIY projects in refurbishment or new build. It can also be used on curved applications.

Pro's

■ UV resistant


Calliclad has many advantages as can be seen below. With its easy installation, 10 year colour guarantee and with virtually no maintenance - Calliclad easily stands the test of time



colour guarantee

Dimensions

Due to their light weight (4kg/plank) and manageable dimensions Calliclad planks can be easily installed. One pack contains 6 planks allowing to cover 1,68m².



Colors

Calliclad is available in different colors and with its 10 year color guarantee there is no need to repaint.



The Calliclad can also be painted.

Easy to install in 7 steps

The installation of Calliclad is both quick and easy with the planks screwed onto vertical wooden batons.

Universal corner profiles are also available in matching colors to give your DIY project that perfect finish.

Step 1: Fit the supporting structure.

Step 2: Fix the sealing profile.

Step 3: Staple joint tape onto the battens.

Step 4: Fix the aluminum Calliclad finishing profile.

Step 5: Fix the starting batten.

Step 6: Measure and cut the planks.

Step 7: Fix the planks.

You will find more installation information on our website www.callibo.com.

Watch the installation video at: www.callibo.com/installation

Accessories

Calliclad aluminium finishing profile: universal profile for interior corner, exterior corner and facade end finishing, available in the colors of the planks (length 3,0 mt).



Black joint tape (PE): to be stapled onto the vertical supporting structure (roll 30 mt).



Perforated aluminium sealing profile for sealing cavity at bottom (length 2,5 mt).

